

iQ100, Gas hob, 60 cm, Stainless steel
EB6B5PB60



HZ298105	Simmer plate
HZ298114	Small pot support

A gas cooktop with side-mounted controls.

✓ Biomethane ready – Power your gas hob with renewable biomethane gas.

Product name/family: gas hob w integrated controls

Built-in / Free-standing: Built-in

Source of energy: Gas

Number of cooking zones: 4

Type of control setting devices:sword knobs

Required niche size for installation (HxWxD):45 x 560-562 x 480-492 mm

Width of the appliance: 580 mm

Dimensions: 56x580x510 mm

Dimensions of the packed product (HxWxD): ... 168 x 798 x 596 mm

Weight: 7.1 kg

Gross weight: 8.0 kg

Residual heat indicator:without

Location of control panel: Lateral

Basic surface material: Stainless steel

Color of surface: Stainless steel

Length electrical supply cord: 100.0 cm

EAN code:4242003687062

Gas connection rating: 7400 W

Fuse protection:3 A

Nominal power:220-240 V

Frequency: 60; 50 Hz

4 242003 687062

iQ100, Gas hob, 60 cm, Stainless steel EB6B5PB60

Design

- Stainless steel surface
- cast iron finish pan supports with rubber feet

Usage convenience

- Design co-ordinated control dials: access knobs on the side with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 4 burner gas hob including:
- Left front: High-speed burner up to 3 KW (depending on gas type)
- Left rear: Standard burner up to 1.7 KW (depending on gas type)
- Right rear: Standard burner up to 1.7 KW (depending on gas type)
- Right front: Economy burner up to 1 KW (depending on gas type)

Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 56 x 580 x 510
- Required niche size for installation (HxWxD mm) : 45 x 560 x (480 - 492)
- Min. worktop thickness: 30 mm
- Power cord: 1 m
- Connected load: 7.4 KW

iQ100, Gas hob, 60 cm, Stainless steel
EB6B5PB60

