

DH45MAWSZ

SDS-max Rotary Hammer Drill

230V - 45 mm

0000000000000

NEW

LVH



High drilling and demolishing performance

Low Vibration Handle

Variable speed control

Specifications

Capacity drill bit	45 mm
Capacity core bit	125 mm
Power input	1,400 W
Impact energy	11.3 J
No-load speed	260 - 380 /min.
Full-load impact rate	1,750 - 2,900 /min.
Full-load vibration level	14.1 m/s ²
No-load noise level	86.4 dB
Full-load noise level	96.2 dB
Dimensions (L x H x W)	535 x 287 x 120 mm
Weight ¹	9.4 kg

Characteristics

- High drilling and demolishing performance for reduced work time
- Low Vibration Handle (LVH) for user protection as well as optimal work comfort and grip
- Large trigger switch for easy grip and best control
- Variable speed control dial for various applications and settings
- One-push bit mounting allows to exchange SDS-max drill bits and chisels with only one action instead of the usual two
- Easy operation thanks to up-sized change lever on top of the tool's body
- Chisels can be rotated by 12 different angles for various applications
- Needle-pin type slip clutch for high slip torque accuracy and enhanced durability

Standard accessories²

- Injection case
- Side handle
- Hammer grease A (30 g)

¹ Weight according to EPTA-2004 procedure.

² Standard accessories vary by country or area.

Read everything
about our services at
[hikoki-powertools.com](https://www.hikoki-powertools.com)

