



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

BOSTIK FP 404 FIRE RETARDANT PU FOAM
Supersedes date 24-Jul-2024

Revision date 16-Apr-2026
Revision Number 5

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK FP 404 FIRE RETARDANT PU FOAM

Other means of identification

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Building and construction work

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Romania SRL
51, Rasaritului Street (DN7)
070000 Buftea
Ilfov
Romania
Phone: +40 372 833 300
Fax: +40 372 833 301
www.bostik.com

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

Ireland **NPIC - National Poison Information Centre**
Members of the Public: +353 (01) 8092166 (8.00 am to 10.00 pm - 7 days a week)
Healthcare Professionals: +353 (01) 8092566 (24 hour service)

United Kingdom Bostik: +44 (1785) 272650 (9am to 5pm Mon-Fri)

Europe 112

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosols	Category 1 - (H222, H229)
Acute toxicity - Inhalation (Dusts/Mists)	Category 4 - (H332)
Skin irritation	Category 2 - (H315)
Eye irritation	Category 2 - (H319)
Respiratory sensitisation	Category 1 - (H334)
Skin sensitisation	Category 1 - (H317)
Carcinogenicity	Category 2 - (H351)
Specific target organ toxicity (single exposure)	Category 3 - (H335)
Specific target organ toxicity (repeated exposure)	Category 2 - (H373)
Hazardous to the aquatic environment - chronic	Category 3 - (H412)

2.2. Label elements

SAFETY DATA SHEET

BOSTIK FP 404 FIRE RETARDANT PU FOAM
Supersedes date 24-Jul-2024

Revision date 16-Apr-2026
Revision Number 5

Contains Diphenylmethane-diisocyanate, isomers and homologues; Reaction products of phosphoryl trichloride and 2-methyloxirane



Signal word
Danger

Hazard statements

H222 - Extremely flammable aerosol.
H229 - Pressurised container: May burst if heated.
H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H332 - Harmful if inhaled.
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 - May cause respiratory irritation.
H351 - Suspected of causing cancer.
H373 - May cause damage to organs through prolonged or repeated exposure.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand
P102 - Keep out of reach of children
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P211 - Do not spray on an open flame or other ignition source
P251 - Do not pierce or burn, even after use
P260 - Do not breathe vapours/spray
P271 - Use only outdoors or in a well-ventilated area
P273 - Avoid release to the environment
P280 - Wear protective gloves and eye/face protection
P302 + P352 - IF ON SKIN: Wash with plenty of water and soap
P304 + P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing
P342 + P311 - If experiencing respiratory symptoms: Call a POISON CENTER or doctor
P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
P405 - Store locked up
P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F
P501 - Dispose of contents/container in accordance with local, regional, national, and international regulations as applicable

Special provisions concerning the labelling of certain mixtures

Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used. As from 24 August 2023 adequate training is required before industrial or professional use.

Additional information

This product requires tactile warnings if supplied to the general public. Placed on the market in aerosol containers or in containers fitted with a sealed spray attachment.

2.3. Other hazards

During transportation by car the cans should stand upright in the cargo space. In case of insufficient ventilation and/or through

SAFETY DATA SHEET

BOSTIK FP 404 FIRE RETARDANT PU FOAM
Supersedes date 24-Jul-2024

Revision date 16-Apr-2026
Revision Number 5

use, the formation of an explosive/highly flammable mixture is possible. The mentioned hazards are valid for the non-reacted content of the can or of the fresh foam. When foaming the propellants are highly flammable. May be harmful if swallowed.

PBT & vPvB

The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors.

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	Weight-%	REACH registration number	EC No. (Index No.)	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	M-Factor	M-Factor (long-term)	Notes
Diphenylmethane-dii socyanate, isomers and homologues 9016-87-9	40 - <80	[7]	618-498-9	STOT SE 3 (H335) STOT RE 2 (H373) Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Resp. Sens. 1 (H334) Skin Sens. 1 (H317) Carc. 2 (H351) Acute Tox. 4 (H332)	-	-	-	-
Reaction products of phosphoryl trichloride and 2-methyloxirane 1244733-77-4	10 - <20	01-2119486772-26-XXXX	807-935-0	Acute Tox. 4 (H302) Carc. 2 (H351) Aquatic Chronic 3 (H412)	-	-	-	-
Isobutane 75-28-5	5 - <10	01-2119485395-27-XXXX	200-857-2 (601-004-00-0)	Flam. Gas 1 (H220) Press. Gas (H280)	-	-	-	C,U
Dimethyl ether 115-10-6	5 - <10	01-2119472128-37-XXXX	204-065-8 (603-019-00-8)	Flam. Gas 1 (H220) Press. Gas (H280)	-	-	-	U
1,2-Benzenedicarboxylic acid, 3,4,5,6-tetrabromo-, mixed esters with diethylene glycol and propylene glycol 77098-07-8	1 - <2.5	01-2119480176-36-XXXX	-	Aquatic Chronic 2 (H411)	-	-	-	-
Butane 106-97-8	0.1 - <1	01-2119474691-32-XXXX	203-448-7 (601-004-00-0)	Flam. Gas 1 (H220) Press. Gas (H280)	-	-	-	C,U
Propylene carbonate 108-32-7	0.1 - <1	01-2119537232-48-XXXX	203-572-1 (607-194-00-1)	Eye Irrit. 2 (H319)	-	-	-	-
Diethylene glycol 111-46-6	0.1 - <0.3	01-2119457857-21-XXXX	203-872-2 (603-140-00-6)	Acute Tox. 4 (H302)	-	-	-	-
Diethylene glycol 111-46-6	0.1 - <0.3	01-2119457857-21-XXXX	203-872-2 (603-140-00-6)	Acute Tox. 4 (H302) STOT RE 2 (H373)	-	-	-	-

Substances identified by a number starting "RR-" in the CAS-field are substances for which the CAS# is not adopted in EU and we use an internal numbering system to track within our SDS software

NOTE [7] - No registration number is given for this substance because it is a polymer exempted from registration according to

SAFETY DATA SHEET

BOSTIK FP 404 FIRE RETARDANT PU FOAM
Supersedes date 24-Jul-2024

Revision date 16-Apr-2026
Revision Number 5

the provisions of Article 2(9) of REACH. All monomers or other substances within the polymer are registered or exempt from registration

Note C - Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note U - When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.), Press. Gas (Liq.), Press. Gas (Ref. Liq.), Press. Gas (Diss.). Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

Full text of H- and EUH-phrases: see section 16

Acute Toxicity Estimate

If LD50/LC50 data is not available or does not correspond to the classification category, then the appropriate conversion value from CLP Annex I, Table 3.1.2, is used to calculate the acute toxicity estimate (ATEmix) for classifying a mixture based on its components

Chemical name	EC No. (Index No.)	CAS No.	Oral LD50 mg/kg	Dermal LD50 mg/kg	Inhalation LC50 - 4 hour - dust/mist - mg/L	Inhalation LC50 - 4 hour - vapour - mg/L	Inhalation LC50 - 4 hour - gas - ppm
Diphenylmethane-diisocyanate, isomers and homologues	618-498-9	9016-87-9	-	-	1.5	-	-
Reaction products of phosphoryl trichloride and 2-methyloxirane	807-935-0	1244733-77-4	632	-	-	-	-
Isobutane	200-857-2 (601-004-00-0)	75-28-5	-	-	-	-	-
Dimethyl ether	204-065-8 (603-019-00-8)	115-10-6	-	-	-	-	-
Butane	203-448-7 (601-004-00-0)	106-97-8	-	-	-	-	-
Propylene carbonate	203-572-1 (607-194-00-1)	108-32-7	-	-	-	-	-
Diethylene glycol	203-872-2 (603-140-00-6)	111-46-6	1120	-	-	-	-
Diethylene glycol	203-872-2 (603-140-00-6)	111-46-6	1120	-	4.6046	-	-

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice	Show this safety data sheet to the doctor in attendance. IF exposed or concerned: Get medical advice/attention.
Inhalation	Remove to fresh air. May cause allergic respiratory reaction. If breathing has stopped, give artificial respiration. Get medical attention immediately. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation.
Eye contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open

SAFETY DATA SHEET

BOSTIK FP 404 FIRE RETARDANT PU FOAM
Supercedes date 24-Jul-2024

Revision date 16-Apr-2026
Revision Number 5

	while rinsing. Do not rub affected area. Get medical attention if irritation develops and persists.
Skin contact	May cause an allergic skin reaction. In the case of skin irritation or allergic reactions see a doctor. Wash off immediately with soap and plenty of water for at least 15 minutes. Do not use solvents or thinners to dissolve the material.
Ingestion	May produce an allergic reaction. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get immediate medical attention. Clean mouth with water. Drink 1 or 2 glasses of water.
Self-protection of the first aider	Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Avoid contact with skin, eyes or clothing. Avoid direct contact with skin. Use barrier to give mouth-to-mouth resuscitation. Use personal protective equipment as required. See section 8 for more information. Avoid breathing vapours or mists.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms	May cause allergy or asthma symptoms or breathing difficulties if inhaled. Coughing and/or wheezing. Itching. Rashes. Hives. Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing. Erythema (skin redness). May cause redness and tearing of the eyes. Burning sensation. Difficulty in breathing.
Effects of Exposure	May cause damage to organs through prolonged or repeated exposure. Suspected of causing cancer.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors	May cause sensitisation in susceptible persons. Treat symptomatically.
------------------------	--

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media	Dry chemical. Carbon dioxide (CO ₂). Water spray. Alcohol resistant foam.
Unsuitable extinguishing media	Full water jet. DO NOT EXTINGUISH A LEAKING GAS FIRE UNLESS LEAK CAN BE STOPPED.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. Cylinders may rupture under extreme heat. Damaged cylinders should be handled only by specialists. Containers may explode when heated. Product is or contains a sensitiser. May cause sensitisation by inhalation. May cause sensitisation by skin contact.
Hazardous combustion products	Carbon oxides. Carbon monoxide. Carbon dioxide (CO ₂). Phosphorus oxides. Nitrogen oxides (NO _x). Hydrogen cyanide. Isocyanates. Bromine compounds. Halogenated compounds.

5.3. Advice for firefighters

Special protective equipment and precautions for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protective equipment.
---	--

SECTION 6: Accidental release measures

SAFETY DATA SHEET

BOSTIK FP 404 FIRE RETARDANT PU FOAM
Supersedes date 24-Jul-2024

Revision date 16-Apr-2026
Revision Number 5

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Take precautionary measures against static discharges. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid breathing vapours or mists.
Other information	Ventilate the area. Refer to protective measures listed in Sections 7 and 8.
For emergency responders	Use personal protection recommended in Section 8.

6.2. Environmental precautions

Environmental precautions	Refer to protective measures listed in Sections 7 and 8. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Methods for containment	Stop leak if you can do it without risk. A vapour suppressing foam may be used to reduce vapours. Dyke far ahead of spill to collect run-off water. Keep out of drains, sewers, ditches and waterways. Flood with water to complete polymerization and scrape off floor.
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labelled containers. Use clean non-sparking tools to collect absorbed material.
Prevention of secondary hazards	Residues which cannot be recycled are disposed of as chemical waste. Equipment cleaned with organic solvent, washings are collected and disposed of as solvent waste. Eliminate all ignition sources if safe to do so.

6.4. Reference to other sections

Reference to other sections	See section 8 for more information. See section 13 for more information.
------------------------------------	--

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling	Use personal protective equipment. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Use spark-proof tools and explosion-proof equipment. Handle product only in closed system or provide appropriate exhaust ventilation. Keep in an area equipped with sprinklers. Do not puncture or incinerate cans. Contents under pressure. In case of rupture. Avoid breathing vapours or mists. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash it before reuse.
General hygiene considerations	Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. Remove and wash contaminated clothing and gloves, including the inside, before re-use.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions	Protect from sunlight. Keep away from heat, sparks, flame and other sources of ignition
---------------------------	---

SAFETY DATA SHEET

BOSTIK FP 404 FIRE RETARDANT PU FOAM
Supersedes date 24-Jul-2024

Revision date 16-Apr-2026
Revision Number 5

(i.e., pilot lights, electric motors and static electricity). Keep in properly labelled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations. Store in a cool, dry area away from potential sources of heat, open flames, sunlight or other chemicals. Store locked up. Keep out of the reach of children. Keep/store only in original container. Store in a dry place. Store in a closed container. Protect from moisture.

Recommended storage temperature Do not freeze.

7.3. Specific end use(s)

Specific use(s)
 Building and construction work.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure Limits

Chemical name	European Union	Ireland	United Kingdom
Diphenylmethane-diisocyanate, isomers and homologues 9016-87-9	TWA: 6 µg/m ³ ; TWA: 10 µg/m ³ ;	TWA: 0.02 mg/m ³ ; STEL: 0.07 mg/m ³ (all, except Methyl isocyanate and 2,4-Toluene diisocyanate or 2,6-Toluene diisocyanate);	TWA: 0.02 mg/m ³ ; STEL: 0.07 mg/m ³ ; poS
Isobutane 75-28-5	-	TWA: 1000 ppm (8hr) STEL: 1000 ppm	
Dimethyl ether 115-10-6	TWA: 1000 ppm; TWA: 1920 mg/m ³ ;	TWA: 1000 ppm; TWA: 1920 mg/m ³ ; STEL: 3000 ppm (calculated); STEL: 5760 mg/m ³ (calculated);	TWA: 400 ppm; TWA: 766 mg/m ³ ; STEL: 500 ppm; STEL: 958 mg/m ³ ;
4,4-Methylenediphenyl diisocyanate 101-68-8	TWA: 10 µg NCO / m ³ (2.9 ppb) STEL: 20 µg NCO / m ³ (5.8 ppb) Sk* +	TWA: 0.005 ppm; STEL: 0.015 ppm (calculated);	TWA: 0.02 mg/m ³ ; STEL: 0.07 mg/m ³ ; poS
Propane 74-98-6	-	STEL: 3000 ppm (calculated); Sa	
Butane 106-97-8	-	STEL: 1000 ppm;	TWA: 600 ppm; TWA: 1450 mg/m ³ ; STEL: 750 ppm; STEL: 1810 mg/m ³ ;
Diethylene glycol 111-46-6	-	TWA: 23 ppm; TWA: 100 mg/m ³ ; STEL: 69 ppm (calculated); STEL: 300 mg/m ³ (calculated);	TWA: 23 ppm; TWA: 101 mg/m ³ ; STEL: 69 ppm; STEL: 303 mg/m ³ ;
Diethylene glycol 111-46-6	-	TWA: 23 ppm; TWA: 100 mg/m ³ ; STEL: 69 ppm (calculated); STEL: 300 mg/m ³ (calculated);	TWA: 23 ppm; TWA: 101 mg/m ³ ; STEL: 69 ppm; STEL: 303 mg/m ³ ;

Derived No Effect Level (DNEL) No information available

SAFETY DATA SHEET

BOSTIK FP 404 FIRE RETARDANT PU FOAM
Supersedes date 24-Jul-2024

Revision date 16-Apr-2026
Revision Number 5

Derived No Effect Level (DNEL)			
Reaction products of phosphoryl trichloride and 2-methyloxirane (1244733-77-4)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	8.2 mg/m ³	
worker Short term Systemic health effects	Inhalation	22.6 mg/m ³	
worker Long term Systemic health effects	Dermal	2.91 mg/kg bw/d	

Dimethyl ether (115-10-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	1894 mg/m ³	

Propylene carbonate (108-32-7)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	70.53 mg/m ³	
worker Long term Local health effects	Inhalation	20 mg/m ³	
worker Long term Systemic health effects	Dermal	20 mg/kg bw/d	
worker Long term Local health effects	Dermal	10 mg/cm ²	

Diethylene glycol (111-46-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	44 mg/m ³	
worker Long term Local health effects	Inhalation	60 mg/m ³	
worker Long term Systemic health effects	Dermal	43 mg/kg bw/d	

Diethylene glycol (111-46-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Inhalation	44 mg/m ³	
worker Long term Local health effects	Inhalation	60 mg/m ³	

SAFETY DATA SHEET

BOSTIK FP 404 FIRE RETARDANT PU FOAM
Supersedes date 24-Jul-2024

Revision date 16-Apr-2026
Revision Number 5

worker Long term Systemic health effects	Dermal	4440 mg/kg bw/d	
--	--------	-----------------	--

Derived No Effect Level (DNEL)

Reaction products of phosphoryl trichloride and 2-methyloxirane (1244733-77-4)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	1.45 mg/m ³	
Consumer Short term Systemic health effects	Inhalation	5.6 mg/m ³	
Consumer Long term Systemic health effects	Dermal	1.04 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	0.52 mg/kg bw/d	
Consumer Short term Systemic health effects	Oral	2 mg/kg bw/d	

Dimethyl ether (115-10-6)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	471 mg/m ³	

Propylene carbonate (108-32-7)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	17.4 mg/m ³	
Consumer Long term Local health effects	Inhalation	10 mg/m ³	
Consumer Long term Systemic health effects	Dermal	10 mg/kg bw/d	
Consumer Long term Systemic health effects	Oral	10 mg/kg bw/d	

Diethylene glycol (111-46-6)

Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	12 mg/m ³	
Consumer Long term Local health effects	Inhalation	12 mg/m ³	
Consumer Long term Systemic health effects	Dermal	21 mg/kg	

SAFETY DATA SHEET

BOSTIK FP 404 FIRE RETARDANT PU FOAM
Supersedes date 24-Jul-2024

Revision date 16-Apr-2026
Revision Number 5

Diethylene glycol (111-46-6)			
Type	Exposure route	Derived No Effect Level (DNEL)	Safety factor
Consumer Long term Systemic health effects	Inhalation	12 mg/m ³	
Consumer Long term Local health effects	Inhalation	12 mg/m ³	
Consumer Long term Systemic health effects	Dermal	21 mg/kg bw/d	
Consumer Long term Systemic health effects	Inhalation	12 mg/m ³	
Consumer Long term Local health effects	Inhalation	12 mg/m ³	
Consumer Long term Systemic health effects	Dermal	21 mg/kg bw/d	

Predicted No Effect Concentration (PNEC) No information available.

Predicted No Effect Concentration (PNEC)	
Reaction products of phosphoryl trichloride and 2-methyloxirane (1244733-77-4)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.32 mg/l
Marine water	0.032 mg/l
Sewage treatment plant	19.1 mg/l
Freshwater sediment	11.5 mg/kg dry weight
Marine sediment	1.15 mg/kg dry weight
Soil	0.34 mg/kg dry weight
Freshwater - intermittent	0.51 mg/l

Dimethyl ether (115-10-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.155 mg/l
Marine water	0.016 mg/l
Microorganisms in sewage treatment	160 mg/l
Freshwater sediment	0.681 mg/kg dry weight
Soil	0.45 mg/kg dry weight

Propylene carbonate (108-32-7)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	0.9 mg/l
Marine water	0.09 mg/l
Soil	0.81 mg/kg dry weight
Sewage treatment plant	7400 mg/l

Diethylene glycol (111-46-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	10 mg/l
Marine water	1 mg/l
Sewage treatment plant	199 mg/l
Freshwater sediment	20.9 mg/kg dry weight
Marine sediment	2.09 mg/kg dry weight
Soil	1.53 mg/kg dry weight
Freshwater - intermittent	10 mg/l

SAFETY DATA SHEET

BOSTIK FP 404 FIRE RETARDANT PU FOAM
Supersedes date 24-Jul-2024

Revision date 16-Apr-2026
Revision Number 5

Diethylene glycol (111-46-6)	
Environmental compartment	Predicted No Effect Concentration (PNEC)
Freshwater	10 mg/l
Marine water	1 mg/l
Sewage treatment plant	199 mg/l
Freshwater sediment	20.9 mg/kg dry weight
Marine sediment	2.09 mg/kg dry weight
Soil	1.53 mg/kg dry weight
Freshwater - intermittent	10 mg/l

8.2. Exposure controls

Engineering controls	Ensure adequate ventilation, especially in confined areas. Vapours/aerosols must be exhausted directly at the point of origin.
Personal protective equipment	
Eye/face protection	Wear safety glasses with side shields (or goggles). Eye protection must conform to standard EN 166
Hand protection	Wear suitable gloves. Butyl rubber. Nitrile rubber. Glove thickness > 0.4 mm. The breakthrough time of the gloves depends on the material and the thickness as well as the temperature. The breakthrough time for the mentioned glove material is in general greater than 60 min. Gloves must conform to standard EN 374
Skin and body protection	Wear appropriate personal protective clothing to prevent skin contact.
Respiratory protection	Ensure adequate respiratory protection during spray applications. In case of insufficient ventilation, wear suitable respiratory equipment.
Recommended filter type:	Organic gases and vapours filter conforming to EN 14387. Wear a respirator conforming to EN 140 with Type A filter or better. AX.
Environmental exposure controls	No information available.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid
Appearance	Aerosol Foam
Colour	Pink
Odour	Characteristic. Slight.

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
Melting point / freezing point	No data available	No data available
Initial boiling point and boiling range	.	Not applicable, Aerosol
Flammability	No data available	Not applicable for liquids
Flammability Limit in Air		None known
Upper flammability or explosive limits	18.6 Vol%	
Lower flammability or explosive limits	1.7 Vol%	
Flash point	No data available	Not applicable, Aerosol
Autoignition temperature	. °C	No data available
Decomposition temperature		No data available
pH	No data available	No data available.
pH (as aqueous solution)	No data available	No data available
Kinematic viscosity	No data available	No data available
Dynamic viscosity	No data available	None known
Water solubility	Insoluble in water.	Reacts with water Polymerisation can occur
Solubility(ies)	No data available	No data available
Partition coefficient	No data available	No data available
Vapour pressure	6 - 6.5	bar @ 23 °C
Relative density	No data available	None known
Bulk density	No data available	

SAFETY DATA SHEET

BOSTIK FP 404 FIRE RETARDANT PU FOAM
Supersedes date 24-Jul-2024

Revision date 16-Apr-2026
Revision Number 5

Liquid Density	1.0332 g/cm ³	
Relative vapour density	No data available	No data available
Particle characteristics		
Particle Size	No information available	
Particle Size Distribution	No information available	

9.2. Other information

Solid content (%)	No information available	
VOC content		No data available

9.2.1. Information with regards to physical hazard classes

Not applicable

9.2.2. Other safety characteristics

No information available

Minimum Ignition Temperature (°C)	235 . Not applicable
-----------------------------------	----------------------

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity	No information available.
------------	---------------------------

10.2. Chemical stability

Stability	Stable under normal conditions.
-----------	---------------------------------

Explosion data

Sensitivity to mechanical impact	None.
Sensitivity to static discharge	Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions	Heating causes rise in pressure with risk of bursting.
------------------------------------	--

10.4. Conditions to avoid

Conditions to avoid	Product cures with moisture. Heat, flames and sparks. Excessive heat. Protect from moisture. Keep away from open flames, hot surfaces and sources of ignition. Extremes of temperature and direct sunlight.
---------------------	---

10.5. Incompatible materials

Incompatible materials	Strong acids. Strong bases. Strong oxidising agents. Water. Alcohols. Amines. Incompatible with oxidising agents.
------------------------	---

10.6. Hazardous decomposition products

Hazardous decomposition products	None under normal use conditions. Stable under recommended storage conditions.
----------------------------------	--

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

SAFETY DATA SHEET

BOSTIK FP 404 FIRE RETARDANT PU FOAM
Supersedes date 24-Jul-2024

Revision date 16-Apr-2026
Revision Number 5

Inhalation	Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Specific test data for the substance or mixture is not available. May cause sensitisation in susceptible persons. (based on components). May cause irritation of respiratory tract. Harmful by inhalation.
Eye contact	Specific test data for the substance or mixture is not available. Causes serious eye irritation. (based on components). May cause redness, itching, and pain.
Skin contact	Specific test data for the substance or mixture is not available. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. (based on components). May cause sensitisation by skin contact. Causes skin irritation.
Ingestion	Specific test data for the substance or mixture is not available. May cause additional effects as listed under "Inhalation". Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms	Symptoms of allergic reaction may include rash, itching, swelling, trouble breathing, tingling of the hands and feet, dizziness, lightheadedness, chest pain, muscle pain, or flushing. Coughing and/ or wheezing. Itching. Rashes. Hives. Redness. May cause redness and tearing of the eyes.
-----------------	--

Acute toxicity

Numerical measures of toxicity

The following ATE values have been calculated for the mixture

ATEmix (oral)	3,878.40 mg/kg
ATEmix (dermal)	>2000 mg/kg
ATEmix (inhalation-gas)	>20000 ppm
ATEmix (inhalation-dust/mist)	3.14 mg/L
ATEmix (inhalation-vapour)	>20 mg/L

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Diphenylmethane-diisocyanate, isomers and homologues	LD50 > 10000 mg/kg (Rattus)	LD 50 > 9400 mg/kg (Oryctolagus cuniculus)	1.5 mg/L (Rattus) 4 h
Reaction products of phosphoryl trichloride and 2-methyloxirane	LD50 > 500 - 2000 mg/kg (males); LD50 = 632 mg/kg (females)(Rattus)	LD50 >2000 mg/Kg (Rattus) (OECD 402)	LD50 >7 mg/L (4h)(Rattus) (OECD 403)
Isobutane	-	-	=658 mg/L (Rattus) 4 h
Dimethyl ether	-	-	=164000 ppm (Rattus) 4 h
1,2-Benzenedicarboxylic acid, 3,4,5,6-tetrabromo-, mixed esters with diethylene glycol and propylene glycol	LD50 > 2000 mg/kg (Rattus)	> 20000 mg/kg (Rabbit)	-
Butane	-	-	=658 g/m ³ (Rattus) 4 h
Propylene carbonate	LD50 > 5000 mg/kg (Rattus) OECD 401	> 3000 mg/kg (Oryctolagus cuniculus)	-
Diethylene glycol	=1120 mg/kg bw (human)	= 11890 mg/kg (Oryctolagus cuniculus)	LC0 (4h)> 4600 mg/m ³ (Rattus)
Diethylene glycol	=1120 mg/kg bw (human)	= 11890 mg/kg (Oryctolagus cuniculus)	>4600 mg/m ³ (Rattus) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

SAFETY DATA SHEET

BOSTIK FP 404 FIRE RETARDANT PU FOAM
Supersedes date 24-Jul-2024

Revision date 16-Apr-2026
Revision Number 5

Skin corrosion/irritation Classification based on data available for ingredients. Causes skin irritation.

Diphenylmethane-diisocyanate, isomers and homologues (9016-87-9)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 404: Acute Dermal Irritation/Corrosion	Rabbit				Mild skin irritant

Reaction products of phosphoryl trichloride and 2-methyloxirane (1244733-77-4)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD 404	Rabbit	Dermal			Non-irritant

Serious eye damage/eye irritation Classification based on data available for ingredients. Causes serious eye irritation.

Reaction products of phosphoryl trichloride and 2-methyloxirane (1244733-77-4)					
Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD 405	Rabbit	eye			Non-irritant

Respiratory or skin sensitisation May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Contains a known or suspected carcinogen. Classification based on data available for ingredients. Suspected of causing cancer.

Component Information		
Diphenylmethane-diisocyanate, isomers and homologues (9016-87-9)		
Method	Species	Results
OECD Test No. 453: Combined Chronic Toxicity/Carcinogenicity Studies	Rat	Carcinogenic

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure May cause respiratory irritation.

STOT - repeated exposure May cause damage to organs through prolonged or repeated exposure.

H373 - May cause damage to the following organs through prolonged or repeated exposure: Lungs, Inhalation.

Aspiration hazard Based on available data, the classification criteria are not met.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties Based on available data, the classification criteria are not met.

SAFETY DATA SHEET

BOSTIK FP 404 FIRE RETARDANT PU FOAM
Supersedes date 24-Jul-2024

Revision date 16-Apr-2026
Revision Number 5

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity Harmful to aquatic life with long lasting effects.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea	M-Factor	M-Factor (long-term)
Diphenylmethane-diisocyanate, isomers and homologues 9016-87-9	ErC50 (72h) >1640 mg/L Algae (scenedesmus subspicatus) (OECD 201)	CL50 (96h) >1000 mg/L Danio rerio	-	EC50 (24H) >1000 mg/L Daphnia magna		
Reaction products of phosphoryl trichloride and 2-methyloxirane 1244733-77-4	EC50 (72h) = 82 mg/L (Pseudokirchneriella subcapitata) OECD 201	LC50 (96h) = 51 mg/L (Pimephales promelas) Static	-	LC50 (48h) = 131 mg/L Daphnia magna		
Dimethyl ether 115-10-6	-	LC50: >4.1g/L (96h, Poecilia reticulata)	-	> 4400 mg/L (Daphnia) (NEN 6501)		
Propylene carbonate 108-32-7	ErC50 (72h): > 900mg/L (Desmodesmus subspicatus, OECD-201)	LC50 (96) h > 1000 mg/L (Cyprinus carpio, 67/548/EWG, Annex V, C.1.)	EC50 > 10000 mg/L 17 h	EC50 (48h): > 1000mg/L (Daphnia magna, OECD 202)		
Diethylene glycol 111-46-6	-	LC50: =75200mg/L (96h, Pimephales promelas)	-	EC50: =84000mg/L (48h, Daphnia magna)		
Diethylene glycol 111-46-6	-	LC50: =75200mg/L (96h, Pimephales promelas)	EC50 = 29228 mg/L 15 min	EC50: =84000mg/L (48h, Daphnia magna)		

12.2. Persistence and degradability

Persistence and degradability No information available.

Diphenylmethane-diisocyanate, isomers and homologues (9016-87-9)			
Method	Exposure time	Value	Results
OECD Test No. 302C: Inherent Biodegradability: Modified MITI Test (II)	28 days	0% biodegradation	Not readily biodegradable

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Reaction products of phosphoryl trichloride and	2.68

SAFETY DATA SHEET

BOSTIK FP 404 FIRE RETARDANT PU FOAM
Supersedes date 24-Jul-2024

Revision date 16-Apr-2026
Revision Number 5

2-methyloxirane	
Isobutane	2.8
Dimethyl ether	-0.18
Butane	2.31
Propylene carbonate	-0.41
Diethylene glycol	-1.98
Diethylene glycol	-1.98

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment The product does not contain any substance(s) classified as PBT or vPvB above the threshold of declaration.

Chemical name	PBT and vPvB assessment
Reaction products of phosphoryl trichloride and 2-methyloxirane	Not PBT/vPvB
Isobutane	Not PBT/vPvB
Dimethyl ether	Not PBT/vPvB
1,2-Benzenedicarboxylic acid, 3,4,5,6-tetrabromo-, mixed esters with diethylene glycol and propylene glycol	Not PBT/vPvB
Butane	Not PBT/vPvB
Propylene carbonate	Not PBT/vPvB
Diethylene glycol	Not PBT/vPvB
Diethylene glycol	Not PBT/vPvB

12.6. Endocrine disrupting properties Endocrine disrupting properties

Endocrine disruption for the environment Based on available data, the classification criteria are not met.

12.7. Other adverse effects Other adverse effects

Other adverse effects No information available.

PMT or vPvM properties Based on available data, the classification criteria are not met.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or weld containers. Handle contaminated packages in the same way as the product itself.

European Waste Catalogue
08 05 01* waste isocyanates
16 05 04* gases in pressure containers (including halons) containing dangerous substances
17 06 04 insulation materials other than those mentioned in 17 06 01 and 17 06 03

Other information Waste codes should be assigned by the user based on the application for which the product was used.

SECTION 14: Transport information

SAFETY DATA SHEET

BOSTIK FP 404 FIRE RETARDANT PU FOAM
Supersedes date 24-Jul-2024

Revision date 16-Apr-2026
Revision Number 5

Note: Keep from freezing.

Land transport (ADR/RID)

14.1 UN number or ID number UN1950
14.2 UN proper shipping name Aerosols
14.3 Transport hazard class(es) 2
Labels 2.1
14.4 Packing group Not regulated
Description UN1950, Aerosols, 2, (D)
14.5 Environmental hazards No
14.6 Special precautions for user
Special Provisions 190, 327, 344, 625
Classification code 5F
Tunnel restriction code (D)
Limited quantity (LQ) 1 L

IMDG

14.1 UN number or ID number UN1950
14.2 UN proper shipping name Aerosols
14.3 Transport hazard class(es) 2.1
14.4 Packing group Not regulated
Description UN1950, Aerosols, 2.1
14.5 Marine pollutant NP
14.6 Special precautions for user
Special Provisions 63,190, 277, 327, 344, 381, 959
Limited Quantity (LQ) See SP277
EmS-No. F-D, S-U
14.7 Maritime transport in bulk according to IMO instruments
Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number UN1950
14.2 UN proper shipping name Aerosols, flammable
14.3 Transport hazard class(es) 2.1
14.4 Packing group Not regulated
Description UN1950, Aerosols, flammable, 2.1
14.5 Environmental hazards No
14.6 Special precautions for user
Special Provisions A145, A167, A802
Limited quantity (LQ) 30 kg G
ERG Code 10L

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

Registration, Evaluation, Authorisation, and Restriction of Chemicals (REACH) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration $\geq 0.1\%$ (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product contains one or more substance(s) subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

SAFETY DATA SHEET

BOSTIK FP 404 FIRE RETARDANT PU FOAM
Supersedes date 24-Jul-2024

Revision date 16-Apr-2026
Revision Number 5

Chemical name	CAS No.	Restricted substance per REACH Annex XVII
Diphenylmethane-diisocyanate, isomers and homologues	9016-87-9	56 74.
Diisocyanates	--	74

56 . If product supplied to the general public with substance $\geq 0.1\%$, then gloves must be provided with the product. **74** If product supplied to the industrial or professional users with total monomeric diisocyanates $\geq 0.1\%$, then its packaging must mention "As from 24 August 2023 adequate training is required before industrial or professional use".

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Export Notification requirements

This product does not contain substances which are regulated pursuant to Regulation (EC) No. 649/2012 of the European parliament and of the council concerning the export and import of dangerous chemicals above the level that triggers a labeling obligation under Regulation (EC) No 1272/2008. Therefore this product is not subject to prior informed consent notification.

Dangerous substance category per Seveso Directive (2012/18/EU)

P3a - FLAMMABLE AEROSOLS

Ozone-depleting substances (ODS) regulation (EC) 2024/590

Not applicable

Persistent Organic Pollutants

Not applicable

REGULATION (EU) 2019/1148 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 20 June 2019 on the marketing and use of explosives precursors

Not applicable

Regulations on drug precursors (EC) No 111/2005 (export) and 273/2004 (internal trade)

This product does not contain any substance(s) on the Drug Precursors list.

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of any hazard and/or precautionary statements referred to under Sections 2-15

H220 - Extremely flammable gas
H280 - Contains gas under pressure; may explode if heated
H302 - Harmful if swallowed
H315 - Causes skin irritation
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H332 - Harmful if inhaled

SAFETY DATA SHEET

BOSTIK FP 404 FIRE RETARDANT PU FOAM
Supersedes date 24-Jul-2024

Revision date 16-Apr-2026
Revision Number 5

H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335 - May cause respiratory irritation
H351 - Suspected of causing cancer
H373 - May cause damage to organs through prolonged or repeated exposure
H411 - Toxic to aquatic life with long lasting effects
H412 - Harmful to aquatic life with long lasting effects

Notes relating to the identification, classification and labelling of substances

Note C - Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers
Note U - When put on the market gases have to be classified as 'Gases under pressure', in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.), Press. Gas (Liq.), Press. Gas (Ref. Liq.), Press. Gas (Diss.). Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2)

SVHC: Substances of Very High Concern for Authorisation:
PBT: Persistent, Bioaccumulative, and Toxic (PBT) Substances
vPvB: Very Persistent and very Bioaccumulative (vPvB) Substances
STOT RE: Specific target organ toxicity - Repeated exposure
STOT SE: Specific target organ toxicity - Single exposure
EWC: European Waste Catalogue
LOW: List of Wastes (see <http://ec.europa.eu/environment/waste/framework/list.htm>)
ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
IATA: International Air Transport Association
ICAO: ICAO-TI: Technical Instructions for the Safe Transport of Dangerous Goods by Air
IMDG: International Maritime Dangerous Goods
RID: Regulations concerning the International Carriage of Dangerous Goods by Rail

Legend SECTION 8: Exposure controls/personal protection

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
AGW	Occupational exposure limit value	BGW	Biological limit value
Ceiling	Maximum limit value	Sk*	Skin designation

Classification procedure	
Classification according to Regulation (EC) No. 1272/2008 [CLP]	Method Used
Acute oral toxicity	Calculation method
Acute dermal toxicity	Calculation method
Acute inhalation toxicity - gas	Calculation method
Acute inhalation toxicity - vapour	Calculation method
Acute inhalation toxicity - dust/mist	Calculation method
Skin corrosion/irritation	Calculation method
Serious eye damage/eye irritation	Calculation method
Respiratory sensitisation	Calculation method
Skin sensitisation	Calculation method
Mutagenicity	Calculation method
Carcinogenicity	Calculation method
Reproductive toxicity	Calculation method
STOT - single exposure	Calculation method
STOT - repeated exposure	Calculation method
Chronic aquatic toxicity	Calculation method
Acute aquatic toxicity	Calculation method
Aspiration hazard	Calculation method
Ozone	Calculation method
Flammable aerosol	On basis of test data

Key literature references and sources for data used to compile the SDS

European Food Safety Authority (EFSA)
European Chemicals Agency (ECHA) Committee for Risk Assessment (ECHA_RAC)
European Chemicals Agency (ECHA) (ECHA_API)

SAFETY DATA SHEET

BOSTIK FP 404 FIRE RETARDANT PU FOAM
Supersedes date 24-Jul-2024

Revision date 16-Apr-2026
Revision Number 5

U.S. Environmental Protection Agency
Acute Exposure Guideline Level(s) (AEGL(s))
International Uniform Chemical Information Database (IUCLID)
Japan National Institute of Technology and Evaluation (NITE)
NIOSH (National Institute for Occupational Safety and Health)
International Organization for Economic Co-operation and Development (OECD) Environment, Health, and Safety Publications
International Organization for Economic Co-operation and Development (OECD) High Production Volume Chemicals Program
International Organization for Economic Co-operation and Development (OECD) Screening Information Data Set

Prepared By Product Safety & Regulatory Affairs

Revision date 16-Apr-2026

Training Advice AS FROM 24 AUGUST 2023 ADEQUATE TRAINING IS REQUIRED BEFORE INDUSTRIAL OR PROFESSIONAL USE
For further information, please contact:
<https://www.safeusediisocyanates.eu/>

Further information No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)
Regulation (EC) No. 1907/2006 as amended by Regulation (EU) No. 2020/878, and Regulation (EC) No. 1272/2008

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet