


N 30, GAS HOB, 60 CM, STAINLESS STEEL
T26BKP6N0



Optional accessories

Z1365WX0	Wireless food thermometer
Z2402X0	Small pot support
Z2480X0	Simmer plate
Z9404SE0	4 pieces Set
Z9406SE0	6 pieces Set

The gas hob with lateral dials with more space in the gaps - for easy cleaning.

- ✓ Sword Dials: Easy control and easy cleaning.
- ✓ Cast Iron Finish Pan Supports: Stability for your pots and pans.
- ✓ Gas Safety Cut-Off: Safety first! No flame, no gas flow.
- ✓ Biomethane Ready: Power your hob with renewable biomethane gas.

Features

Technical Data

Product name/family:gas hob w
integrated controls
Built-in / Free-standing: Built-in
Energy input: Gas
Number of cooking zones: 4
Type of control setting devices: sword knobs
Required niche size for installation (HxWxD): 45 x 560-560 x
480-490 mm
Width of the appliance: 580 mm
Dimensions: 51.8x580x510 mm
Dimensions of the packed product (HxWxD): . 141 x 651 x 578 mm
Net weight: 6.8 kg
Gross weight: 7.6 kg
Residual heat indicator: Without
Location of control panel: Lateral
Basic surface material: Stainless steel
Color of surface: Stainless steel
Length electrical supply cord: 100 cm
EAN code: 4242004284512
Gas connection rating: 7500 W
Fuse protection: 3 A
Voltage: 220-240 V
Frequency: 50; 60 Hz



N 30, GAS HOB, 60 CM, STAINLESS STEEL T26BKP6N0

Features

Design

- Stainless steel surface
- Cast iron finish pan supports with rubber feet

Usage convenience

- Design co-ordinated control dials, right: access knobs on the side with strong grip for effortless turning.
- Ignition via control dials: just push and turn the dials to ignite the flame.

Burners and power

- 4 burner hob
- Left front: High-speed burner up to 3 KW (depending on gas type)
- Left rear: Standard burner up to 1.75 KW (depending on gas type)
- Right rear: Standard burner up to 1.75 KW (depending on gas type)
- Right front: Economy burner up to 1 KW (depending on gas type)

Cleaning

- Wider distance between dials for better cleaning.

Safety

- Flame failure safety device: prevents unwanted gas flow when flame goes out.

Installation (gas types & measurements)

- Usable for: Nat gas L/LL G25/20mbar(DE)
- NG H/E 20mbar, E+ 20/25mbar Natural gas H 25 mbar (HU) Natural gas L 25 mbar (NL) Liquid gas G30,31 28-30/37mbar Liquid gas G30 37 mbar (PL) Liquid gas 50 mbar
- Factory set for connection to mains gas
- Nozzle set for LPG jets (28-30/37mbar) included. Nozzles for all other gas types can be ordered via the customer service. For nozzle change, please contact the customer service.
- Dimensions of the product (HxWxD mm): 51.8 x 580 x 510
- Required niche size for installation (HxWxD mm) : 45 x 560 x (480 - 490)
- Min. worktop thickness: 20 mm
- Power cord: 1 m
- Connected load: 7.5 KW

N 30, GAS HOB, 60 CM, STAINLESS STEEL
T26BKP6N0

Dimensioned drawings

