CONSTRUCTION PRODUCT REGULATION DECLARATION OF PERFORMANCE

No: TDS00427

Product Description:	EVO-STIK Fast Set Floor Tile Adhesive for Wood & Concrete Floors	
Product Code:	30812924	
Intended Use:	Fast setting ready mixed adhesive for internal tiling	
Manufacturer: Contact Address:	Bostik Ltd Ulverscroft Road Leicester LE4 6BW	
System of Assessment:	System 3	
Harmonised Standard:	EN12004:2007+A1:2012	
Notified Body:	The notified body No.NB1289 carried out the determination of the product type on the basis of type testing on samples taken by the manufacturer under system 3 and issued the test report (131338)–5708	

Declared Performance: C1F		
Essential Characteristics	Performance	Harmonised technical specification
Reaction to fire	F	
Initial Tensile adhesion strength	≥ 0.5 N/mm2	
Tensile adhesion strength after water immersion	≥ 0.5 N/mm2	
Tensile adhesion strength after heat aging	≥ 0.5 N/mm2	
Tensile adhesion strength after freeze thaw cycles	≥ 0.5 N/mm2	EN998-1:2010
Open time: tensile adhesion strength	≥ 0.5 N/mm2 after not less than 20 min	
Early tensile adhesion strength	≥ 0.5 N/mm²	
Open time: tensile adhesion strength	≥ 0.5 N/mm2 after not less than 10 min	
Dangerous substances	See MSDS	

The performance of the product EVO-STIK Fast Set Floor Tile Adhesive for Wood & Concrete Floors is in conformity with the declared performance shown in the table above.

This declaration of performance is issued under the sole responsibility of Bostik Ltd.

Signed for and on behalf of Bostik Ltd by:

Name: Alison Jamieson

Function: S.H.E.Q. Manager

Signature:

A Jamesz

Date: April 2014

Bostik Limited, Common Road, Stafford, ST16 3EH, UK. Tel: +44 (0) 1785 272625 <u>www.bostik.com/uk</u> Bostik, Evo-Stik & Sealocrete are registered trademarks of Bostik Ltd.