



Issued 08/14

???

## NON-DRIP GLOSS

**Dulux** Non-Drip Gloss is easy to use, as it resists drips and runs and does not require an undercoat. It is suitable for both inside and outside on wood and metal surfaces, including radiators. It gives long lasting beauty and protection.

### KEY BENEFITS

- Resists drips & runs
- Long-lasting protection
- No undercoat required

### PRODUCT INFORMATION

#### Typical Use

Suitable for use on interior and exterior wood and metal surfaces, including radiators.

#### Pack Size

750ml and 2.5L

#### Colour Range

PBW

#### Film Properties

**Chemical Resistance:** Resistant to mild chemical fume attack, but where there is heavy attack, such as actual contact with chemicals, specialist paint systems may be required (contact the **Dulux** Technical advice.)

**Heat Resistance:** Generally resistant to heat up to 90°C, but some discolouration of light colours may occur at elevated temperatures.

**Water Resistance:** Resistant to the levels of atmospheric humidity present in normal interior and exterior environments and will withstand repeated washing. Not suitable for immersed surfaces or where is very heavy and

prolonged condensation.

#### Composition (nominal)

**Pigment:** Lightface non-Lead Pigments

**Binder:** Alkyd

**Solvent:** White Spirit

#### Volume Solids

White 63% (nominal) other colours may vary.

### SURFACE PREPARATION

To get the best results with **Dulux** Non-drip Gloss, make sure surfaces to be painted are sound, clean and dry (new surfaces particularly must be fully dry).

Remove all loose and defective paint. Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

Where necessary, wash the surface to remove dirt, grease and powdery or dusty residues. Rinse with clean water and allow to dry. Seal surfaces that remain powdery after thorough preparation with an appropriate plaster sealer.

Where necessary, rub down and then wipe off with a damp, lint free cloth to avoid dust.

Any surface defects should be filled with the appropriate **Polycell** Trade **Polyfilla**.



???

## NON-DRIP GLOSS

### SYSTEMS INFORMATION

STIR THOROUGHLY BEFORE USE. Apply straight from the can using a suitable clean brush. Do not overspread the paint. For the best results, where a strong colour change is required, two coats may be necessary.

Where a second coat of Non-Drip Gloss is required allow a minimum of 16 hours between coats.

For improved obliteration on rough or textured surfaces, or when using special process colours, (clean colours) 2 coats of Dulux Non-Drip Gloss will be required in order to achieve full opacity

Note: Whilst leading-edge technology has been used in the development of this product, the nature of white solvent based paints means that they will all discolour over time. The rate of discolouration is faster on areas with no or low natural or UV light. For longer lasting whiteness, we recommend the use of a water-based formulation Dulux Aquatech Stay White Gloss.

For best colour consistency, purchase sufficient tinted paint for each job including touch-in at one time from the same source.

### APPLICATION METHOD

Brush or Roller. For Health and Safety reasons relating to solvent based paint, spray application is not recommended.

As with other solvent based paints, do not apply in temperatures below 5°C (as recommended by British Standard BS 6150)

#### Practical Coverage

A guide to the practical coverage which can be achieved under normal conditions is up to 12m<sup>2</sup> per litre.

#### Drying Times

Single coat of standard thickness:

**Touch Dry:** 4-6 Hours

**Re-coat:** 16-24 Hours

#### Cleaning Up

After use, remove as much product as possible from equipment before cleaning with brush cleaner.

When this paint container is empty please ask your stockist about recycling. If you have leftover paint, please dispose of it responsibly and consider donating it to

**Community RePaint.** Find out more at [dulux.ie](http://dulux.ie)

#### Transportation & Storage

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

#### VOC

EU limit for this product (cat: A/d): 300g/l (2010). This product contains max. 300g/l VOC. VOC Content: High (25-50%).



???

Issued 08/14

## NON DRIP GLOSS

### FURTHER SUPPORT

If you need further support, please contact the **Dulux** Technical Advice Centre on **+353-21-422-0222**

***Always read full Health, Safety & Environmental Information on can before use.***

Safety datasheet (SDS 411) is available free on request by telephoning the **Dulux** Technical Advice Centre or by visiting ***dulux.ie***

AkzoNobel, the AkzoNobel logo, the Flourish logo, Dulux Trade, Mouldshield, Polycell, Polyfilla, Community RePaint and the Planet Possible logo are trademarks of the AkzoNobel group. © AkzoNobel 2014.



At Dulux Trade, we believe by working with our customers we can reduce waste and do more with the resources we have. Together we can create a better future for our planet. Join us at [duluxtrade.co.uk/pp](http://duluxtrade.co.uk/pp)

**AkzoNobel**