## PRODUCT SPECIFICATION



## 8MM DYNAMIC 4V 32 / AC4

PRODUCT RANGE	INFORMATION	
Floor Type	Laminate floor	
Features & Finish	1-Strip	
Board Size	1380 X 193 X 8mm	
Box Quantity	8 Boards per pack	
Pack Size	2.131m <sup>2</sup>	
Packs per pallet	56 Packs per pallet	
Use Class	32 / AC4	
Origin	Made in Germany	
Bevel	4V	
Bathroom	No	
Conservatory	Yes	
Under Floor Heating	Yes	
Warranty	25 Year residential / 3 year commercial according to terms of our warranty	
Installation	5G click system	
DOP	WD_LF_001 Available on request with our office or can be downloaded on www.wrg.ie.	
EUTR	Responsibly sourced under EUTR regulations	

TEST	CHARACTERISTICS	TEST METHOD
Formaldehyde emission	< 0.05 ppm	EN 717-1
Surface stain resistance	Grade 5, no visible changes to surface	EN 438-2, 15
Lightfastness	≥ Level 6 Blue Wool Scale Level 4 Grey Scale	EN ISO 105-B02 EN 20 105-A02
Resistance to cigarette embers	Grade 4, no visible changes to surface	EN 438-2, 18
Fire resistance	Ignites with difficulty, at least Cfl-s1	EN 13501-1
Height difference between connected elements	Average: ≤ 0.10 mm Max: ≤ 0.15 mm	EN 13329
Edge straightness (bend)	≤ 0.3 mm/m	EN 13329
Openings between connected elements	Average: ≤ 0.15 mm max: ≤ 0.20 mm	EN 13329
Static indentation	< 0.01 mm - no visible changes, Impression in test with straight steel cylinder of 11,3 mm diameter	EN 433

This technical data sheet was developed by Whiteriver Group, Cluide, Dunleer, Co Louth, Ireland, A92 V8YN. At the time of issuing this datasheet, all information is correctly stated. The company reserves the right to update or amend the specifications of this product at any time without prior notice to third parties.

















