

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

**EVO-STIK SILICONE SEALANT MP BLACK** 

Supercedes Date: 10-May-2018

Revision date 21-Jan-2021 Revision Number 2.01

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product Identifier

Product Name EVO-STIK SILICONE SEALANT MP BLACK

Pure substance/mixture Mixture

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Sealant.
Uses advised against None known

## 1.3. Details of the supplier of the safety data sheet

**Company Name** 

Bostik Industries Limited Newtown, Swords Co. Dublin Ireland Tel: +353 (1) 8624900 Fax: +353 (1) 8402186

E-mail address SDS.box-EU@bostik.com

## 1.4. Emergency telephone number

**United Kingdom** +44 (1785) 272650

**treland** +353 (1) 8624900 (Monday- Friday 9am-5pm)

## **SECTION 2: Hazards identification**

## 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

#### 2.2. Label Elements

#### Signal word

None

## **Hazard statements**

### **EU Specific Hazard Statements**

EUH208 - Contains 4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT]. May produce an allergic reaction

EUH210 - Safety data sheet available on request

## **Precautionary statements**

P101 - If medical advice is needed, have product container or label at hand.

P102 - Keep out of reach of children.

P302 + P352 - IF ON SKIN: Wash with plenty of water and soap.

P501 - Dispose of contents/ container to an approved waste disposal plant.

## 2.3. Other Hazards

Small amounts of acetic acid (CAS 64-19-7) are formed by hydrolysis and released upon curing

## PBT & vPvB

**EVO-STIK SILICONE SEALANT MP BLACK** 

Supercedes Date: 10-May-2018 Revision Number 2.01

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

## SECTION 3: Composition/information on ingredients

#### 3.1 Substances

Not applicable

# 3.2 Mixtures

Chemical name	EC No.	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	934-956-3	RR-100252-4	>25 - <40	Asp. Tox. 1 (H304)		01-2119827000- 58-XXXX
Triacetoxy(propyl)silane	241-816-9	17865-07-5	1 - <3	Skin Corr. 1B (H314) (EUH071)		01-2119966899- 07-XXXX
Silanetriol, methyl-, triacetate	224-221-9	4253-34-3	1- <2.5	Skin Corr. 1C (H314) Acute Tox. 4 (H302) (EUH014)		01-2119962266- 32-XXXX
4,5-dichloro-2-octyl-2H-i sothiazol-3-one [DCOIT]	264-843-8	64359-81-5	0.01 - <0.05	Skin Corr. 1B (H314) Eye Dam. 1 (H318) Skin Sens. 1A (H317) Acute Tox. 4 (H302) Acute Tox. 2 (H330) Aquatic Acute 1 (H400) M=100 Aquatic Chronic 1 (410) M=10		

## Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

# **SECTION 4: First aid measures**

### 4.1. Description of first aid measures

General advice Immediate medical attention is required. Show this safety data sheet to the doctor in

attendance.

Inhalation Remove to fresh air. Get medical attention immediately if symptoms occur.

**EVO-STIK SILICONE SEALANT MP BLACK** 

Supercedes Date: 10-May-2018

**Eye contact** Get immediate medical advice/attention. Rinse immediately with plenty of water, also

under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to

Revision date 21-Jan-2021

Revision Number 2.01

do. Continue rinsing. Keep eye wide open while rinsing. Do not rub affected area.

**Skin contact** Wash off immediately with soap and plenty of water for at least 15 minutes. Get medical

attention if irritation develops and persists.

Ingestion Clean mouth with water and drink afterwards plenty of water. Never give anything by

mouth to an unconscious person. Do NOT induce vomiting. Call a doctor.

Self-protection of the first aider Avoid contact with skin, eyes or clothing. Wear personal protective clothing (see section

8).

4.2. Most important symptoms and effects, both acute and delayed

**Symptoms** Burning sensation.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically.

## **SECTION 5: Firefighting measures**

5.1. Extinguishing media

Suitable extinguishing media

Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

**Unsuitable extinguishing media** Full water jet. Do not scatter spilled material with high pressure water streams.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Thermal decomposition can lead to release of toxic and corrosive gases/vapours.

Hazardous combustion products Carbon dioxide (CO2). Silicon dioxide. Thermal decomposition can lead to release of

irritating and toxic gases and vapours.

5.3. Advice for firefighters

Special protective equipment for

fire-fighters

Firefighters should wear self-contained breathing apparatus and full firefighting turnout

gear. Use personal protection equipment.

## SECTION 6: Accidental release measures

#### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use personal

protective equipment as required.

**Other information** Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

**Environmental precautions** Prevent further leakage or spillage if safe to do so.

## 6.3. Methods and material for containment and cleaning up

**EVO-STIK SILICONE SEALANT MP BLACK** 

Supercedes Date: 10-May-2018

Revision date 21-Jan-2021 Revision Number 2.01

and place into a container for later disposal.

Methods for cleaning up Take up mechanically, placing in appropriate containers for disposal.

6.4. Reference to other sections

**Reference to other sections** See section 8 for more information. See section 13 for more information.

# **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Avoid contact

with skin, eyes or clothing. Provide a good standard of controlled ventilation (10 to 15 air changes per hour). Do not eat, drink or smoke when using this product. Take off

contaminated clothing and wash it before reuse.

General hygiene considerations Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection.

Do not eat, drink or smoke when using this product.

#### 7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Store locked up. Keep out of the reach of children. Keep containers tightly closed in a

dry, cool and well-ventilated place.

#### 7.3. Specific end use(s)

## Specific Use(s)

Sealant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

**Other information** Observe technical data sheet.

## SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

**Exposure Limits** Small amounts of acetic acid (CAS 64-19-7) are formed by hydrolysis and released upon

curing

Chemical name	European Union	Ireland	United Kingdom
Acetic acid	TWA: 25 mg/m <sup>3</sup>	TWA: 10 ppm	TWA: 10 ppm
64-19-7	TWA: 10 ppm	TWA: 25 mg/m <sup>3</sup>	TWA: 25 mg/m <sup>3</sup>
	STEL: 50 mg/m <sup>3</sup>	STEL: 20 ppm	STEL: 20 ppm
	STEL: 20 ppm	STEL: 50 mg/m <sup>3</sup>	STEL: 50 mg/m <sup>3</sup>

Derived No Effect Level (DNEL) No information available

**Predicted No Effect Concentration** No information available. **(PNEC)** 

#### 8.2. Exposure controls

**Engineering controls** Ensure adequate ventilation, especially in confined areas. Ensure that enough fresh air

is supplied to dilute and remove dusts, fumes or vapours. Between 5 and 15 air changes

per hour are recommended, with a through draught.

**EVO-STIK SILICONE SEALANT MP BLACK** 

Supercedes Date: 10-May-2018

**Personal Protective Equipment** 

Eye/face protection Wear safety glasses with side shields (or goggles). Eye protection must conform to

standard EN 166.

Wear suitable gloves, Recommended Use:, Neoprene™, Nitrile rubber, Butvl rubber. Hand protection

> Glove thickness > 0.7mm. The breakthrough time for the mentioned glove material is in general greater than 480 min. Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific

Revision date 21-Jan-2021

Revision Number 2.01

gloves. Gloves must conform to standard EN 374

None under normal use conditions. Skin and body protection

Respiratory protection In case of inadequate ventilation wear respiratory protection. Wear a respirator

conforming to EN 140 with Type A/P2 filter or better. Ensure adequate ventilation,

especially in confined areas.

Organic gases and vapours filter conforming to EN 14387. White. Brown. Recommended filter type:

**Environmental exposure controls** Do not allow uncontrolled discharge of product into the environment.

## SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Solid Physical state

Viscous Paste **Appearance** Colour Black Odour Acetic acid

**Odour threshold** No information available

Remarks • Method **Property** Values

No data available pН Melting point / freezing point No data available **Boiling point / boiling range** No data available Flash point > 100 °C **Evaporation rate** No data available

Flammability (solid, gas) Not applicable for liquids .

Flammability Limit in Air

Upper flammability or explosive No data available

limits

Lower flammability or explosive No data available

limits

Vapour pressure No data available No data available Relative vapour density No data available Relative density

Water solubility Product cures with moisture

No data available Solubility(ies) Partition coefficient No data available **Autoignition temperature** No data available **Decomposition temperature** No data available Kinematic viscosity  $> 21 \text{ mm}^2/\text{s}$ **Dynamic viscosity** No data available No data available **Explosive properties Oxidising properties** No data available

9.2. Other information

Solid content (%) No information available No information available **VOC Content (%)** 

**Density** 0.97

## SECTION 10: Stability and reactivity

#### 10.1. Reactivity

**EVO-STIK SILICONE SEALANT MP BLACK** 

Supercedes Date: 10-May-2018 Revision Number 2.01

**Reactivity** No information available.

10.2. Chemical stability

Stability Stable under normal conditions.

**Explosion data** 

Sensitivity to mechanical

None.

impact

Sensitivity to static discharge None.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

Conditions to avoid None known based on information supplied.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

**Hazardous decomposition** 

products

None under normal use conditions. Stable under recommended storage conditions.

## **SECTION 11: Toxicological information**

#### 11.1. Information on toxicological effects

Information on likely routes of exposure

Product Information

**Inhalation** Specific test data for the substance or mixture is not available.

**Eye contact** Specific test data for the substance or mixture is not available.

**Skin contact** Specific test data for the substance or mixture is not available.

**Ingestion** Specific test data for the substance or mixture is not available. Ingestion may cause

gastrointestinal irritation, nausea, vomiting and diarrhoea.

Symptoms related to the physical, chemical and toxicological characteristics

**Symptoms** Burning. May cause blindness. Redness. May cause redness and tearing of the eyes.

Numerical measures of toxicity

**Acute toxicity** 

#### **Component Information**

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Hydrocarbons, C15-C20,	LD50 > 5000 mg/kg (Rattus)	LD50 > 3160 mg/kg	LC50 Inhalation(4h) >5266
n-alkanes, isoalkanes, cyclics,	OECD 401	(Oryctolagus cuniculus)	MG/M3 (Rattus)

**EVO-STIK SILICONE SEALANT MP BLACK** 

Supercedes Date: 10-May-2018

Revision date 21-Jan-2021 Revision Number 2.01

< 0.03% aromatics RR-100252-4		OECD 402	
Silanetriol, methyl-, triacetate 4253-34-3	LD50 = 1600 mg/kg (Rattus) OECD 401		
4,5-dichloro-2-octyl-2H-isothiaz ol-3-one [DCOIT] 64359-81-5	=1636 mg/kg (Rattus)	> 2000 mg/kg (Oryctolagus cuniculus)	=0.26 mg/L (Rattus) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation The assessment of the result of testing was done in accordance with the guideline of the

Commission 92/69/EEC.

Product Information					
Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	Dermal			Non-irritant
	Rabbit	Dermal		6 days	Product score <=1
					Non-irritant

**Serious eye damage/eye irritation** By analogy to another tested similar product: No irritation after contact to the eyes. (H318 is void).

Product Information					
Method	Species	Exposure route	Effective dose	Exposure time	Results
	Rabbit	eye			Non-irritant

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Component Information				
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] (64359-81-5)				
Method	Species	Exposure route	Results	
OECD Test No. 406: Skin	Guinea pig		sensitising	
Sensitisation			_	

Germ cell mutagenicity Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure**Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

## **SECTION 12: Ecological information**

12.1. Toxicity

**Ecotoxicity** Harmful to aquatic life.

Chemical name	Algae/aguatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor

**EVO-STIK SILICONE SEALANT MP BLACK** 

Supercedes Date: 10-May-2018 Revision Number 2.01

	plants		microorganisms			(long-term)
Hydrocarbons,	EL50 (72h)	LL50 (96h) >	-	LL50 (48h)>		
C15-C20, n-alkanes,	>10,000 mg/L	1028 mg/L		3193 mg/l		
isoalkanes, cyclics, <	(Skeletonema	(Scophthalmus		(Acartia tonsa)		
0.03% aromatics	costatum)	maximus)				
RR-100252-4	ISO 10253	OECD 203				
Triacetoxy(propyl)silan	EC50 (72h):	LC50 (96h) =	-	EC50 (48h) =		
е	approx. 24	108.89 mg/L		89.59 mg/L		
17865-07-5	mg/I(Pseudokirc					
	henriella					
	subpicata)					
Silanetriol, methyl-,	EC50 (72h):	LC50 (96h)	-	EC50 (48h)		
triacetate	>500 mg/l	>500 mg/l		>500 mg/l		
4253-34-3	(Pseudokirchner	` ,		(Daphnia		
	ella subcapitata)	rerio)		magna)		
4,5-dichloro-2-octyl-2H-	EC50 (72h)	LC50 (96h)	-	EC50 (48h)	100	10
isothiazol-3-one	=0.025 mg/L	0.0078 mg/L		0.0097 mg/L		
[DCOIT]	Algae	(Oncorhynchus		Daphnia magna		
64359-81-5	(Scenedesmus	mykiss)(OECD		(OECD 202)		
	subspicatus)(OE	203)				
	CD 201)					

## 12.2. Persistence and degradability

Persistence and degradability No information available.

Component Information				
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] (64359-81-5)				
Method	Exposure time	Value	Results	
OECD Test No. 308: Aerobic and		Half-life	1.1-1.3 days	
Anaerobic Transformation in				
Aquatic Sediment Systems				

## 12.3. Bioaccumulative potential

**Bioaccumulation** There is no data for this product.

## **Component Information**

Chemical name	Partition coefficient	Bioconcentration factor (BCF)
Triacetoxy(propyl)silane	1.23	-
17865-07-5		
Silanetriol, methyl-, triacetate 4253-34-3	-2.4	-
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] 64359-81-5	4.4	13

# 12.4. Mobility in soil

Mobility in soil No information available.

## 12.5. Results of PBT and vPvB assessment

## PBT and vPvB assessment

Chemical name	PBT and vPvB assessment
Hydrocarbons, C15-C20, n-alkanes, isoalkanes, cyclics, < 0.03% aromatics	The substance is not PBT / vPvB
RR-100252-4	
Triacetoxy(propyl)silane	The substance is not PBT / vPvB

**EVO-STIK SILICONE SEALANT MP BLACK** 

Supercedes Date: 10-May-2018 Revision Number 2.01

17865-07-5	
Silanetriol, methyl-, triacetate 4253-34-3	The substance is not PBT / vPvB
4,5-dichloro-2-octyl-2H-isothiazol-3-one [DCOIT] 64359-81-5	The substance is not PBT / vPvB

#### 12.6. Other adverse effects

Other adverse effects No information available.

## SECTION 13: Disposal considerations

## 13.1. Waste treatment methods

Waste from residues/unused

products

Dispose of contents/container in accordance with local, regional, national, and

international regulations as applicable.

Contaminated packaging Do not reuse empty containers. Handle contaminated packages in the same way as the

product itself.

**European Waste Catalogue** 08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous

substances

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

## **SECTION 14: Transport information**

#### Land transport (ADR/RID)

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable

14.6 Special Provisions None

#### **IMDG**

14.1 UN number or ID number
14.2 Proper Shipping Name
14.3 Transport hazard class(es)
14.4 Packing group
Not regulated
Not regulated
Not regulated
Not regulated
Not regulated
Not regulated

14.5 Marine pollutantNP14.6 Special ProvisionsNone

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code Not applicable

### Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID numberNot regulated14.2 Proper Shipping NameNot regulated14.3 Transport hazard class(es)Not regulated14.4 Packing groupNot regulated14.5 Environmental hazardsNot applicable14.6 Special ProvisionsNone

# Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

**EVO-STIK SILICONE SEALANT MP BLACK** 

Supercedes Date: 10-May-2018

**European Union** 

#### Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

#### **SVHC: Substances of Very High Concern for Authorisation:**

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

#### EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

#### Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

## Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

#### **Persistent Organic Pollutants**

Not applicable

## National regulations

### 15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. Chemical Safety Assessment has been carried out for this mixture

## **SECTION 16: Other information**

## Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

EUH014 - Reacts violently with water

EUH071 - Corrosive to the respiratory tract

H302 - Harmful if swallowed

H304 - May be fatal if swallowed and enters airways

H314 - Causes severe skin burns and eye damage

H317 - May cause an allergic skin reaction

H318 - Causes serious eye damage

H330 - Fatal if inhaled

H400 - Very toxic to aquatic life

## Legend

TWA TWA (time-weighted average) STEL (Short Term Exposure Limit) STEL

Ceiling Ceiling Limit Value Skin designation

**SVHC** Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

Specific target organ toxicity - Repeated exposure STOT RE STOT SE Specific target organ toxicity - Single exposure

**EWC** European Waste Catalogue Revision date 21-Jan-2021

Revision Number 2.01

**EVO-STIK SILICONE SEALANT MP BLACK** 

Supercedes Date: 10-May-2018 Revision Number 2.01

#### Key literature references and sources for data

No information available

Prepared By Product Safety & Regulatory Affairs

Revision date 21-Jan-2021

Indication of changes

**Revision note** SDS sections updated, 8, 11.

Training Advice No information available

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

#### Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**